Serial No. 10/823,634

IN THE CLAIMS:

Please AMEND claim 95 as indicated below:

- 1-91. (CANCELED)
- 92. (PREVIOUSLY PRESENTED) An apparatus comprising:

a first compensator compensating wavelength dispersion, the first compensator having a constant wavelength dispersion characteristic over a plurality of wavelengths; and

a second compensator compensating wavelength dispersion after wavelength dispersion is compensated by the first compensator, wherein the first and second compensators together compensate for wavelength dispersion dependent on a respective wavelength of a transmission line.

- 93. (PREVIOUSLY PRESENTED) An apparatus as in claim 92, further comprising: a housing which houses, and thereby encloses, both the first and second compensators.
- 94. (PREVIOUSLY PRESENTED) An apparatus as in claim 92, further comprising: a substrate on which both the first and second compensators are fixed.
- 95. (CURRENTLY AMENDED) An apparatus as in claim 92 claim 93, further comprising:

a substrate on which both the first and second compensators are fixed.

- 96. (PREVIOUSLY PRESENTED) An apparatus as in claim 92, wherein the respective wavelength is the wavelength of a respective signal light included in a wavelength division multiplexed (WDM) light transmitted through the transmission line and including a plurality of signal lights at different wavelength multiplexed together.
- 97. (PREVIOUSLY PRESENTED) An apparatus as in claim 92, wherein the first compensator is a virtually imaged phased array (VIPA) dispersion compensator.
 - 98. (PREVIOUSLY PRESENTED) An apparatus comprising:

first means for compensating wavelength dispersion, the first means having a constant wavelength dispersion characteristic over a plurality of wavelengths; and

Serial No. 10/823,634

second means for compensating wavelength dispersion after wavelength dispersion is compensated by the first means, wherein the first and second means together compensate for wavelength dispersion dependent on a respective wavelength of a transmission line.

- 99. (PREVIOUSLY PRESENTED) An apparatus as in claim 98, further comprising: a housing which houses, and thereby encloses, both the first and second compensators.
- 100. (PREVIOUSLY PRESENTED) An apparatus comprising:
 a first compensator compensating for wavelength dispersion, the first compensator
 having a constant wavelength dispersion characteristic over a plurality of wavelengths; and
 a second compensator compensating for dispersion slope over the plurality of
 wavelengths after the compensation by the first compensator.
 - 101. (PREVIOUSLY PRESENTED) An apparatus as in claim 100, further comprising: a housing which houses, and thereby encloses, both the first and second compensators.
 - 102. (PREVIOUSLY PRESENTED) An apparatus as in claim 100, further comprising: a substrate on which both the first and second compensators are fixed.
 - 103. (PREVIOUSLY PRESENTED) An apparatus as in claim 101, further comprising: a substrate on which both the first and second compensators are fixed.
- 104. (PREVIOUSLY PRESENTED) An apparatus as in claim 100, wherein the first and second compensators together compensate for dispersion of a respective wavelength of a respective signal light included in a wavelength division multiplexed (WDM) light transmitted through a transmission line and including a plurality of signal lights at different wavelength multiplexed together.
- 105. (PREVIOUSLY PRESENTED) An apparatus as in claim 100, wherein the first compensator is a virtually imaged phased array (VIPA) dispersion compensator.